

Stream-3s-016

16 Channel Compact 1U Network Video Decoder



Technical Specification

System

Operating System	Embedded LINUX
------------------	----------------

Video/Audio

Max IP Channels	16 Channel
Two-way Talk	1 Channel Input, 1 Channel Output, RCA
Audio Encode	G.711A
Audio Decoding	G.711A,G711U,G726

Display

Interface	1 HDMI, 1 VGA, 1CH BNC
Resolution	HDMI: 3840×2160, 1920×1080, 1280×1024, 1280×720 VGA: 1920×1080, 1280×1024, 1280×720
Display Split	1/4/8/9/16
Decoding Capacity	Main Stream: 1ch 8M/4ch 1080P@30FPS/ 8ch 720P@30FPS
Video Compression	H.265/H.264

Alarm

Alarm Input	8ch
Relay Output	4ch NO/NC

Network

Ethernet	1 RJ-45 Ports (10/100/1000Mbps)
Input Bandwidth	96Mbps
Output Bandwidth	40Mbps
Interoperability	Onvif S 2.0

Auxiliary Interface

USB	2 USB Ports (2 USB 2.0)
RS232	N/A
RS485	1ch, Half-Duplex

General

Power Supply	DC +12V 3.3A
Power Consumption	6W
Working Environment	-10°C ~ +55°C (+14°F ~ +131°F) 10-90% humidity
Dimensions (W×D×H)	215mm x 160mm x 45mm (8.4" x 6.3" x 1.8")
Weight	.9kg (1.99 lb)